### (19) World Intellectual Property Organization

International Bureau



## 

(43) International Publication Date 22 September 2005 (22.09.2005)

**PCT** 

# (10) International Publication Number WO 2005/088128 A1

(51) International Patent Classification<sup>7</sup>: F04B 43/06, 43/067, 45/053

(21) International Application Number:

PCT/NZ2005/000046

(22) International Filing Date: 18 March 2005 (18.03.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

531822

18 March 2004 (18.03.2004) NZ

(71) Applicant (for all designated States except US): PRECISION DISPENSING SYSTEMS LIMITED [NZ/NZ]; Aviation Way, Via Poultry Farm Road, Massey University, Palmerston North (NZ).

(72) Inventor; and


(75) Inventor/Applicant (for US only): GRAPES, Robert,

**Donald** [NZ/NZ]; 339 Old West Road, R D 4, Palmerston North (NZ).

- (74) Agent: HOPKINS, Donald, Leslie; c/- Don Hopkins & Associates, Unit 2, Northcote Office Park, 145-147 Queen Street, Palmerston North (NZ).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: A MEMBRANE PUMP



(57) Abstract: A pump that has a cavity (13) in which is located a flexible membrane (14). An inlet (24) opens into the cavity (13) and is associated with a valve (27). A valve (28) is likewise provided in an outlet (25). Also opening into cavity (13) is a port (22) to which means for applying negative and positive pressures can be connected whereby the flexible membrane (14) can be moved to its two states corresponding to completion of inlet and exhaust of a pumping cycle.

## WO 2005/088128 A1

GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### **Published:**

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.